



Residential Steel Doors

• Product Information •

Premium Series
Models HDP20 | HDPF20 | HDPL20
(17.2 HIGH R-VALUE)



3-LAYER CONSTRUCTION



① Steel + ② Insulation + ③ Steel

17.2
R-VALUE
 2" insulation

PRODUCT SPECIFICATIONS

- 27 gauge steel skins and insulation are pressure bonded for durable, secure, quiet operation.
- 2" thick polyurethane foamed-in-place insulation with silicone filled thermal break provides superior energy efficiency. **17.2 R-value.**
- Hot-dipped galvanized steel skin with a baked-on primer and top coat helps assure durability and long-lasting beauty.
- Nylon rollers for durable, smooth, long-lasting performance.
- Patented Safe-T-Bracket® designed for added safety; under normal circumstances it cannot be removed while the door is under tension.
- Tongue-and-groove joints and bottom weatherseal in a rust-proof aluminum retainer helps seal out the elements.
- 12" radius track for normal installations. 15" radius track available.
- Extension springs standard on all single doors (up to and including 10' wide). EZ-SET® torsion springs standard on double doors (greater than 10' wide).
- Inside slide lock is standard, outside keyed lock available (at additional charge).
- Operator reinforcement bracket is standard.

STYLE & FINISH

- Woodgrain texture raised panel and flush designs may be painted with a high quality exterior latex paint to complement any home's exterior.
- Prefinished white end stiles and interior steel provide a clean and finished appearance.

SIZES

- Models HDP20, HDPF20 available in 2" increments from 6'2" to 20' wide.
- Model HDPL20 available only in 8', 9', 10', 12', 14', 15', 15'6", 16', 17', 18', 19', 19'6", and 20' widths.
- Available in 3" increments from 6' to 12' high (excluding 7'3").
- For high lift track applications, please call Clopay customer service.

SPECIAL NOTES

- For doors sold through Home Depot's Expert Installation Program, the springing systems and locking systems may vary by market.
- Doors ordered in white unless a color is specified.

STANDARD HEADROOM REQUIREMENTS


| Extension Springs | | Torsion Springs | |
|-------------------|------------------|-----------------|------------------|
| Track Radius | Headroom Needed* | Track Radius | Headroom Needed* |
| 12" | 10" | 12" | 12" |
| 15" | 12" | 15" | 14" |

* Add 3" for automatic garage door opener.

PANEL OPTIONS



HDP20 (Short Elegant)



HDPF20 (Flush)



HDPL20 (Long Elegant)

COLORS



Brown Gray Hunter Green

(Printed colors may vary from actual panel colors.)

WINDOWS

- Short windows available on Models HDP, HDPF
- Long windows available on Models HDP, HDPF, HDPL
- Palladian™ Series windows available on top section only
- Plain Series and Snap-In Series (Colonial) windows are standard in 2nd section from top, all other windows standard in top section unless specified otherwise

Plain Series



Plain Short

Snap-In Series



Prairie 610

Studio™ Series



Marquise

Palladian™ Series



Long with Grille

See pages S19-S21 for all available window designs and options.

WARRANTIES

